Smart Desktop Terminal

SUNMI T3 New

Power meets elegance at your counter.

Powered by **SUNMI OS** | Compatible with **SUNMI DMP** | Google Mobile Services | ENERGY STAR PARTNER

New platform to unleash powerful performance.

Enjoy a 20% performance boost, with a Qualcomm octa-core processor offering a clock speed up to 2.4GHz and built with a 6nm process technology, along with 4GB RAM+64GB ROM of robust memory.

Sleek Z shape. Consistent excellence in design.

The standout Z-shaped design offers elegance from every angle.
A metal die-casting process provides a slim yet sturdy body.
The hidden cable system keeps your workspace organized and clutter-free.

Enhanced user experience with new features.

Triple displays provide versatile content presentation and seamless multi-screen integration.
The NFC readers on two sides of the screen simplify membership management.
The power button features fingerprint recognition for instant unlocking and secure app access.

SUNMI T3 Tech Specs

CPU Qualcomm Kryo 265 octa-core up to 2.4GHz	**OS** SUNMI OS (based on Android 13)	**Memory** 4GB RAM+64GB ROM	**Display** 15.6" FHD 1920*1080, anti-fingerprint	**Mobile Network** Supports 2G & 3G & 4G (optional)
SIM Card Slot 1* Micro SIM (an option for the 4G Version)	**Wired Network** LAN 1000M	**Wi-Fi** 2.4GHz & 5GHz IEEE 802.11 a/b/g/n/ac supported	**Bluetooth** Bluetooth 5.0 supported BLE supported	**Camera** Front camera, single-lens, 5MP
Card Reader NFC on screen	**External Memory** 1*MicroSD (TF card) Up to 2TB supported	**Speaker** 2* 2W	**Indicator Light** Power indicator light	**Ports** 3*USB 2.0 Type A port 1*USB 3.0 Type A port 1*USB Type C port 2*Micro USB port 1* Micro-USB debug port 1*RJ45 port 1*RJ11 port 1*RJ12 port 1*DC port
Buttons 1*Power button (lock screen and fingerprint recognition) 1*Download button (hidden hole)	**Accessories** 15.6" separate monitor, FHD 1920*1080, capacitive multitouch display 10.1" separate monitor, HD 1280*800, capacitive multitouch display	**Power Adapter** Input: AC 100~240V/1.7A Output: DC 24V/2.5A	**Weight** 5.5kg (with package) 3kg (net)	**Dimensions** 314mm*374mm*170mm
Environment Operating temp.: 0°C-40°C Storage temp.: -20°C~60°C				

*T3 has not been officially launched. Product specifications are subject to the final released version.