

DPT 300

DuraPOS

Durapos, our premium product range, is specifically designed to meet the high demands of modern points of sale, with seamless integration of functionality and reliability at the forefront.



www.duranmatic.nl



- 300 mm/s high printing speed
- 2 Year SWAP warranty

Specifications		Description
Print	Printing method Resolution Printing Speed Printing width	Direct thermal line printing Standard 203dpi (8 dots/mm) / Standard 180dpi (7 dots/mm) Max. 300mm/s 48mm/72mm
Interface	Standard	USB + Serial + Ethernet
Page mode		Support
Barcode	1D 2D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 PDF417, QR code
Fonts	Chinese Alphanumeric User-defined Codepage	GBK 24x24 dots ASCII 9x17, 12x24 dots Yes 48
Memory	RAM Flash	2MB 4MB
Graphics		Support bitmapping with different density and user defined bitmap printing. (Max size of each bitmap is 40K, the total size of bitmap is 256k)
Detection	Sensors	Paper out sensor, two paper near end sensors, cutter jam detection, cover open switch
LED indicator	Paper Power Error	Red LED Green LED Red LED
Reliability	TPH life Cutter life	150KM 2 million cuts
Power supply	Input Output	AC 100v – 240v DC 24V/2.5A
Paper	Paper type Paper width Paper thickness Roll paper diameter Paper load Paper cut	Thermal receipt printer 58mm / 80mm 0.056~0.1mm max. OD Ø83mm Easy paper loading Partial cut
Environment	Operation Storage	0C ~ 45C, 25% ~ 85%RH -30C ~ 60C, 5% ~ 95%RH Physical
Physical Characteristics	Dimension Weight	197(L)x145(W)x146(H)mm 1.8KG
Options & Accessories		USB/serial cable, paper roll, power adapter, power cord, CD, quick start guide
Software	Emulation Driver	ESC/POS XP/Win7/Win8 /Win10 /POSReady/ Linux CUPS/OPOS/JavaPOS
	SDK	WinCE, Win Mobile, Android, iOS

More information about DuraPOS:

- +31 (0)78 65 31 873
- pos@duranmatic.nl
- www.duranmatic.nl

Suitable for:



Retail



Food marts



Hospitality